

Safety Data Sheet

Issue Date: 17-Jun-2016

Revision Date: 05-May-2022

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Angelus Dye Reducer

Other means of identification

SDS # ASP-026

Product Code 861

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Thinner / reducer for leather dyes

Details of the supplier of the safety data sheet

Supplier Address

Dharma Trading Company
1805 South McDowell Blvd. Ext.
Petaluma, CA 94954 USA
(800) 542-5227

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Liquid

Odor Slightly sweet Alcohol odor

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Specific target organ toxicity (single exposure)	Category 1
Flammable Liquids	Category 2

Signal Word

Danger

Hazard statements

Harmful if swallowed
Harmful if inhaled
Causes damage to organs
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Rinse mouth
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Ethyl Alcohol	64-17-5	>40
1-Methoxy-2-propanol	107-98-2	>10
Methanol	67-56-1	<4
Isopropyl Alcohol	67-63-0	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel.
Ingestion	IF SWALLOWED: rinse mouth. Do not induce vomiting without medical advice. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

Most important symptoms and effects

Symptoms	Contact with eyes may cause stinging, tearing, redness, or swelling. Contact with skin may result in redness and burning. If inhaled, symptoms may include, irritation of the nose, throat, and respiratory tract. Swallowing may result in gastrointestinal irritation (nausea, vomiting, and diarrhea), headache, dizziness, shortness of breath, drunken behavior, visual disturbance, fatigue, unconsciousness, complete blindness, and death. Alcohol consumed before or after exposure may worsen effects. Ingestion of moderate quantities of methanol produces acidosis.
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat as methyl alcohol poisoning. Treatment should include the following: Hemodialysis, the intravenous administration of ethanol (10ml per hour) to interfere with the metabolism of methyl alcohol; and the administration of sodium bicarbonate to correct acidosis.
---------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Regular foam, Water fog, Carbon dioxide (CO₂), Dry chemical, Alcohol foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.

Hazardous Combustion Products Carbon monoxide, Carbon dioxide (CO₂), Various hydrocarbons.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively. Water spray may be used to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Persons not wearing protective equipment should leave area until cleanup is completed. Eliminate all ignition sources. Prevent further leakage or spillage if safe to do so. Ventilate area of leak or spill. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up absorbed material and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Do not store above 49°C/120°F.

Packaging Materials Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid).

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
1-Methoxy-2-propanol 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Provide sufficient ventilation to maintain exposure below TLV(s). Any use of this product at an elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Impervious gloves, clothes and boots. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors; Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Slightly sweet Alcohol odor
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined	Remarks • Method	
Property	Values		
pH	Not determined		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	Not determined		

Flash Point	18 °C / 64 °F
Evaporation Rate	3 (butyl acetate = 1)
Flammability (Solid, Gas)	Not determined
Flammability Limits in Air	
Upper Flammability Limits	Not determined
Lower Flammability Limit	Not determined
Vapor Pressure	No data
Vapor Density	No data
Relative Density	No data
Water Solubility	Not determined
Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Auto-ignition Temperature	Not determined
Decomposition Temperature	Not determined
Kinematic Viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

Other Information

VOC Content	741 g/L
Density	7.5 lbs/gal @ 77°F

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from heat, sparks and open flame.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO₂). Various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin and clothing.

Inhalation Harmful if inhaled.

Ingestion Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
1-Methoxy-2-propanol 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h
Methanol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 64000 ppm (Rat) 4 h = 22500 ppm (Rat) 8 h
Oleic Acid 112-80-1	= 25 g/kg (Rat)	-	-
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h

Information on physical, chemical and toxicological effects**Symptoms**

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Isopropyl Alcohol (IPA) is an IARC Monograph Group 3 chemical. IPA is a Group 1 when manufactured by the strong-acid process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X
Isopropyl Alcohol 67-63-0		Group 3		X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - single exposure

Causes damage to organs.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1,864.00 mg/kg

ATEmix (dermal) 6,548.00 mg/kg

ATEmix (inhalation-dust/mist) 8.00 mg/L

ATEmix (inhalation-vapor) 18.00 mg/L

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50	10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50

1-Methoxy-2-propanol 107-98-2		static 4600 - 10000: 96 h Leuciscus idus mg/L LC50 static 20.8: 96 h Pimephales promelas g/L LC50 static	23300: 48 h Daphnia magna mg/L EC50
Methanol 67-56-1		18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	
Oleic Acid 112-80-1		205: 96 h Pimephales promelas mg/L LC50 static	
Isopropyl Alcohol 67-63-0	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	1400000: 96 h Lepomis macrochirus µg/L LC50 9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethyl Alcohol 64-17-5	-0.32
1-Methoxy-2-propanol 107-98-2	-0.437
Methanol 67-56-1	-0.77
Isopropyl Alcohol 67-63-0	0.05

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol 67-56-1		Included in waste stream: F039		U154

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
Ethyl Alcohol 64-17-5	Toxic Ignitable
Methanol 67-56-1	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II

IATA

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II

IMDG

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Marine Pollutant	Yes

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethyl Alcohol	X	X	X	Present	X	Present	X	X
1-Methoxy-2-propanol	X	X	X	Present	X	Present	X	X
Water	X	X	X	X	X	Present	X	X
Methanol	X	X	X	Present	X	Present	X	X
Oleic Acid	X	X	X	Present	X	Present	X	X
Isopropyl Alcohol	X	X	X	Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Methanol - 67-56-1	67-56-1	<4	1.0
Isopropyl Alcohol - 67-63-0	67-63-0	<1	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental
Methanol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethyl Alcohol 64-17-5	X	X	X
1-Methoxy-2-propanol 107-98-2	X	X	X
Methanol 67-56-1	X	X	X
Oleic Acid 112-80-1			X
Isopropyl Alcohol 67-63-0	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	3	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	3	0	Not determined

Issue Date: 17-Jun-2016
 Revision Date: 05-May-2022
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

